

Report No.:

Test Time: 2025-11-11 15:40

Luminaire Property

Luminaire Manufacturer:

Luminaire Category:

Lamp Catalog: 4000K

Number of Lamps:

Luminous Length (mm): 85

Luminous Height (mm):

Current: 0.0340 A

Power Factor: 0.9410

Luminaire Description:

Lamp Description:

Lumens per Lamp:

Luminous Width (mm): 85

Voltage: 231.90 V

Power: 7.32 W

Photometric Results

CIE Class: Direct

Measurement Flux: 791.6 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H89

Vertical Diffuse Angle(50%): V87.4

Luminous Efficacy (lm/w): 108.15

Max. Intensity: 526.02 cd/klm

S/MH(C0/C180): 1.17

Total Rated Lamp Lumens: 791.6 lm

Efficiency: 100%


Upward Ratio: 0%

C0r0 Intensity: 526.02 cd/klm


Pos of Max. Intensity: H0 V0

S/MH(C90/C270): 1.17

Picture Of Luminaire



Luminous Intensity Distribution Curve



Unit: cd/klm

Average Diffuse Angle(50%): 88.2°

— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0



Test Device: GPM-1600L

Distance: 7.172 m [K=1.0000]

Humidity:

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°):0.0-90.0:5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:

Luminous Intensity Distribution Curve(cd/klm)




C Plane (°):0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°):0.0-90.0:5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:

Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1	1.11	1.07	1.04	1.01	1.09	1.05	1.02	0.99	1.01	0.99	0.96	0.97	0.95	0.93	0.94	0.92	0.91	0.89
2	1.03	0.96	0.91	0.86	1.01	0.95	0.90	0.85	0.91	0.87	0.83	0.88	0.85	0.82	0.85	0.82	0.80	0.78
3	0.96	0.87	0.80	0.75	0.93	0.85	0.79	0.74	0.83	0.77	0.73	0.80	0.75	0.72	0.78	0.74	0.71	0.69
4	0.89	0.79	0.71	0.66	0.87	0.77	0.70	0.65	0.75	0.69	0.64	0.73	0.68	0.63	0.71	0.66	0.63	0.61
5	0.82	0.71	0.64	0.58	0.81	0.70	0.63	0.58	0.68	0.62	0.57	0.66	0.61	0.57	0.65	0.60	0.56	0.54
6	0.77	0.65	0.57	0.52	0.75	0.64	0.57	0.51	0.63	0.56	0.51	0.61	0.55	0.51	0.60	0.54	0.50	0.48
7	0.72	0.60	0.52	0.46	0.70	0.59	0.52	0.46	0.58	0.51	0.46	0.56	0.50	0.46	0.55	0.50	0.45	0.44
8	0.67	0.55	0.47	0.42	0.66	0.54	0.47	0.42	0.53	0.46	0.42	0.52	0.46	0.42	0.51	0.45	0.41	0.40
9	0.63	0.51	0.43	0.38	0.62	0.50	0.43	0.38	0.49	0.43	0.38	0.48	0.42	0.38	0.47	0.42	0.38	0.36
10	0.59	0.47	0.40	0.35	0.58	0.47	0.40	0.35	0.46	0.39	0.35	0.45	0.39	0.35	0.44	0.39	0.35	0.33


Spacing Criteria (0-180): 1.17
 Spacing Criteria (90-270): 1.17
 Spacing Criteria (Diagonal): 1.22



C Plane (°):0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°):0.0-90.0:5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:


Isocandela (rectangle)



C Plane (°):0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°):0.0-90.0:5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:

Isocandela (sphere)



Imax (100%): 416 cd

(10%): 42 cd	(16%): 67 cd
(25%): 104 cd	(40%): 167 cd
(63%): 262 cd	(100%): 416 cd


CIE: narrow - short
CIE: Non-cut-off luminaire
Max.At90: 40.165 cd/klm

IES: Non-cut-off
Max.At80: 603.361 cd/klm
Max.80-90: 11379871227193897000000000000000

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: GPM-1600L
Distance: 7.172 m [K=1.0000]
Humidity:
Inspector:

IsoLux Plot



Mounting Height: 10.0m Max Lux(100%): 4.2 lx


(1%): 0.0 lx	(2%): 0.1 lx
(5%): 0.2 lx	(10%): 0.4 lx
(20%): 0.8 lx	(50%): 2.1 lx
(100%): 4.2 lx	

C Plane (°):0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°):0.0-90.0:5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:

Roadway CU Curve

Efficiency(%)





C Plane (°):0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°):0.0-90.0:5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h



L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	39592	32432	24111	16476	11456	10186	8984	8082	7162
C90	36789	28203	19155	12316	10071	8583	7150	5619	4701
C180	40083	33679	25530	17603	12488	11100	10027	9158	8941
C270	39322	30975	21819	14145	10935	9474	8107	6815	5812

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: GPM-1600L

Distance: 7.172 m [K=1.0000]

Humidity:

Inspector:


Illuminance at a Distance



C Plane (°):0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°):0.0-90.0:5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:

Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 416.4 lx

— (1%): 4.2 lx	— (2%): 8.3 lx
— (5%): 20.8 lx	— (10%): 41.6 lx
— (20%): 83.3 lx	— (50%): 208.2 lx
— (100%): 416.4 lx	

C Plane (°):0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°):0.0-90.0:5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:


Area Flux Table

		Unit: lm/klm																				
Vertical plane	-90	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.0	0.0	0.0	1.6	0.0	
	-80	0.0	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.6	0.6	0.6	0.5	0.4	0.3	0.2	0.1	0.0	0.0	5.3	0.0	
	-70	0.0	0.1	0.2	0.4	0.6	0.8	1.1	1.3	1.4	1.3	1.2	1.0	0.8	0.5	0.3	0.2	0.1	0.0	11.2	1.7	
	-60	0.0	0.1	0.3	0.6	1.0	1.6	2.4	3.1	3.6	3.5	3.1	2.3	1.5	0.9	0.5	0.3	0.1	0.0	24.8	20.6	
	-50	0.0	0.1	0.4	0.8	1.7	3.3	5.1	6.7	7.5	7.5	6.6	5.0	3.2	1.6	0.7	0.3	0.1	0.0	50.8	48.4	
	-40	0.0	0.2	0.5	1.2	2.9	5.4	8.0	10.0	11.0	11.0	10.0	8.0	5.4	2.8	1.1	0.4	0.1	0.0	78.0	76.3	
	-30	0.0	0.2	0.5	1.7	4.1	7.2	10.2	12.4	13.5	13.5	12.4	10.2	7.2	4.0	1.6	0.5	0.2	0.0	99.3	98.0	
	-20	0.0	0.2	0.6	2.1	5.0	8.4	11.6	13.8	15.0	15.0	13.8	11.6	8.4	4.9	2.0	0.6	0.2	0.0	113.3	112.2	
	-10	0.0	0.2	0.7	2.4	5.5	9.0	12.2	14.5	15.7	15.7	14.5	12.3	9.0	5.4	2.3	0.6	0.2	0.0	120.2	119.1	
	0	0.0	0.2	0.7	2.4	5.5	9.0	12.2	14.5	15.7	15.7	14.5	12.2	9.0	5.4	2.2	0.6	0.2	0.0	120.0	118.9	
	10	0.0	0.2	0.6	2.1	5.0	8.4	11.5	13.7	14.9	14.9	13.7	11.5	8.4	4.9	2.0	0.6	0.2	0.0	112.6	111.5	
	20	0.0	0.2	0.5	1.6	4.0	7.1	10.0	12.2	13.3	13.3	12.2	10.0	7.1	3.9	1.5	0.5	0.2	0.0	98.0	96.7	
	30	0.0	0.1	0.4	1.1	2.8	5.3	7.8	9.7	10.8	10.8	9.7	7.7	5.2	2.7	1.1	0.4	0.1	0.0	75.9	74.3	
	40	0.0	0.1	0.4	0.8	1.6	3.1	4.8	6.3	7.1	7.1	6.3	4.8	3.0	1.6	0.7	0.3	0.1	0.0	48.1	45.8	
	50	0.0	0.1	0.3	0.5	0.9	1.5	2.2	2.8	3.2	3.2	2.8	2.1	1.4	0.9	0.5	0.2	0.1	0.0	22.8	18.4	
	60	0.0	0.1	0.2	0.3	0.6	0.8	1.0	1.2	1.2	1.2	1.1	1.0	0.7	0.5	0.3	0.2	0.1	0.0	10.4	0.6	
	70	0.0	0.0	0.1	0.2	0.3	0.4	0.5	0.5	0.5	0.5	0.5	0.4	0.4	0.3	0.2	0.1	0.0	0.0	4.9	0.0	
	80	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.0	0.0	0.0	1.4	0.0	
	90	0.3	2.1	6.5	18.4	42.0	72.0	101.3	123.5	135.2	135.1	123.3	100.9	71.3	40.9	17.4	6.0	1.9	0.2	998		
	Flux(T)	0.0	0.0	1.5	14.5	38.5	68.6	98.0	120.2	131.9	131.8	120.0	97.6	68.0	37.4	13.5	1.2	0.0	0.0		943	
	Flux(E)	0.0	0.0	1.5	14.5	38.5	68.6	98.0	120.2	131.9	131.8	120.0	97.6	68.0	37.4	13.5	1.2	0.0	0.0		943	
		-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90	Flux(T)	Flux(E)
		Horizontal plane																				

Gamma Plane (°):0.0-90.0:5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:

C Plane (°):0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

The Average Illuminance Effective Figure



C Plane (°): 0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°): 0.0-90.0: 5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:

UGR Table


Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	22.9	24.1	23.2	24.3	24.6	22.6	23.8	22.9	24.0	24.2
3H	23.2	24.3	23.5	24.5	24.8	22.8	23.9	23.1	24.1	24.4
4H	23.3	24.3	23.7	24.6	24.9	22.9	23.9	23.3	24.2	24.5
6H	23.4	24.3	23.8	24.6	25.0	23.0	23.9	23.3	24.2	24.5
8H	23.5	24.3	23.8	24.6	25.0	23.0	23.9	23.4	24.2	24.5
12H	23.5	24.3	23.8	24.6	25.0	23.0	23.8	23.4	24.2	24.5
X=4H Y=2H	23.0	24.0	23.3	24.3	24.6	22.7	23.7	23.0	24.0	24.3
3H	23.4	24.3	23.8	24.6	24.9	23.1	23.9	23.5	24.2	24.6
4H	23.6	24.4	24.0	24.7	25.1	23.3	24.0	23.7	24.4	24.7
6H	23.8	24.5	24.2	24.8	25.2	23.4	24.0	23.8	24.4	24.8
8H	23.9	24.5	24.3	24.9	25.3	23.4	24.0	23.9	24.4	24.8
12H	23.9	24.5	24.4	24.9	25.3	23.4	24.0	23.9	24.4	24.8
X=8H Y=4H	23.7	24.3	24.1	24.7	25.1	23.3	23.9	23.7	24.3	24.7
6H	23.9	24.4	24.4	24.8	25.3	23.5	24.0	24.0	24.4	24.9
8H	24.0	24.4	24.5	24.9	25.4	23.6	24.0	24.1	24.5	24.9
12H	24.1	24.5	24.6	24.9	25.4	23.6	24.0	24.1	24.5	25.0
X=12H Y=4H	23.6	24.2	24.1	24.6	25.0	23.3	23.8	23.7	24.2	24.7
6H	23.9	24.3	24.4	24.8	25.3	23.5	23.9	24.0	24.4	24.9
8H	24.0	24.4	24.5	24.9	25.4	23.6	24.0	24.1	24.4	24.9
Variations with the observer position at spacings:										
S=1.0H	+0.6/-0.9					+0.7/-1.1				
S=1.5H	+1.3/-2.3					+1.5/-2.6				
S=2.0H	+2.7/-3.2					+2.9/-3.4				

Calculate in accordance with CIE Pub.117. The table is revised with 792lm ($8\log(F/F_0) = -0.8$).

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: GPM-1600L
Distance: 7.172 m [K=1.0000]
Humidity:
Inspector:

LCS Graph



Back Light

Forward Light

Scale= MAX LCS%

Trapped Light:NA,NA

C Plane (°):0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°):0.0-90.0:5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 1.25									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.69	0.79	0.85	0.89	0.95	0.99	1.02	1.05	1.07	
	0.30		0.63	0.73	0.79	0.84	0.90	0.95	0.98	1.02	1.04	
	0.20		0.58	0.68	0.75	0.80	0.87	0.91	0.95	0.99	1.02	
0.50	0.50	0.20	0.68	0.77	0.83	0.87	0.92	0.96	0.98	1.01	1.03	
	0.30		0.62	0.72	0.78	0.82	0.88	0.92	0.95	0.99	1.01	
	0.20		0.58	0.68	0.74	0.79	0.85	0.89	0.92	0.96	0.99	
0.30	0.50	0.20	0.66	0.75	0.81	0.84	0.89	0.93	0.95	0.98	0.99	
	0.30		0.61	0.71	0.77	0.81	0.86	0.90	0.92	0.96	0.98	
	0.20		0.58	0.67	0.73	0.78	0.83	0.87	0.90	0.94	0.96	
0.00	0.00	0.00	0.56	0.65	0.71	0.75	0.80	0.84	0.86	0.89	0.91	
<p>Rating:7W Photometrically tested without ceiling board.</p> <p>Multiply UF values by service correction factors</p> <p>Calculate in accordance with CIBSE Technical Memorandum NO.5 1980</p>												

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: GPM-1600L
Distance: 7.172 m [K=1.0000]
Humidity:
Inspector:

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 1.25									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.81	0.64	0.54	0.46	0.36	0.30	0.26	0.20	0.16	
	0.30		0.67	0.55	0.47	0.41	0.33	0.28	0.24	0.19	0.15	
	0.20		0.58	0.48	0.42	0.37	0.30	0.25	0.22	0.17	0.15	
0.50	0.50	0.20	0.77	0.62	0.51	0.44	0.35	0.32	0.24	0.18	0.15	
	0.30		0.66	0.53	0.45	0.39	0.32	0.26	0.23	0.17	0.14	
	0.20		0.57	0.47	0.41	0.36	0.29	0.24	0.21	0.17	0.14	
0.30	0.50	0.20	0.75	0.59	0.49	0.42	0.33	0.27	0.23	0.17	0.14	
	0.30		0.64	0.52	0.44	0.38	0.30	0.25	0.21	0.17	0.14	
	0.20		0.56	0.46	0.40	0.35	0.28	0.23	0.20	0.16	0.13	
0.00	0.00	0.00	0.44	0.35	0.29	0.25	0.20	0.16	0.14	0.11	0.09	
Rating:7W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

C Plane (°):0.0-360.0: 90.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°):0.0-90.0:5.0
 Test Device: GPM-1600L
 Distance: 7.172 m [K=1.0000]
 Humidity:
 Inspector:

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 1.25								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.15	0.16	0.17	0.18	0.19	0.19	0.20	0.21	0.21
	0.30		0.09	0.11	0.12	0.13	0.15	0.16	0.17	0.18	0.19
	0.20		0.05	0.07	0.09	0.10	0.12	0.14	0.15	0.16	0.17
0.50	0.50	0.20	0.14	0.15	0.16	0.17	0.18	0.19	0.19	0.20	0.20
	0.30		0.09	0.11	0.12	0.13	0.15	0.16	0.17	0.18	0.19
	0.20		0.05	0.07	0.09	0.10	0.12	0.13	0.14	0.16	0.17
0.30	0.50	0.20	0.14	0.15	0.16	0.16	0.17	0.18	0.18	0.19	0.19
	0.30		0.09	0.10	0.12	0.13	0.14	0.15	0.16	0.17	0.18
	0.20		0.05	0.07	0.08	0.10	0.12	0.13	0.14	0.15	0.16
0.00	0.00	0.00	NA	NA	NA	NA	NA	NA	NA	NA	NA
<p>Rating:7W Photometrically tested without ceiling board.</p> <p>Multiply UF values by service correction factors</p> <p>Calculate in accordance with CIBSE Technical Memorandum NO.5 1980</p>											

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: GPM-1600L
Distance: 7.172 m [K=1.0000]
Humidity:
Inspector:

Zonal Lumen

[illegible]

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: GPM-1600L
Distance: 7.172 m [K=1.0000]
Humidity:
Inspector:

Zonal Lumen (Continue 1)

cone flux(90°): 576.85 lm

%lum = 72.9%
%lamp = 72.9%

cone flux(120°): 732.83 lm

%lum = 92.6%
%lamp = 92.6%

Unit: cd/klm

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: GPM-1600L
Distance: 7.172 m [K=1.0000]
Humidity:
Inspector:

LED Average Luminance Report

Avg.L	cd/m ²
L 0-180(65) av	11971.83
L 0-180(75) av	9505.51
L 0-180(85) av	8051.45
L 90-270(65) av	10502.99
L 90-270(75) av	7628.48
L 90-270(85) av	5256.47
L 45(65) av	11237.41
L 45(75) av	8566.99
L 45(85) av	6653.96

Standard: GB/T 29293-2012