

PLEASE READ AND UNDERSTAND ALL WARNINGS, CAUTIONS AND OPERATING INSTRUCTIONS IN THIS MANUAL BEFORE USING THIS EQUIPMENT. Failure to follow all instructions may result in electric shock, fire and/or serious personal injury.


Box Includes:

1 x Weatherproof Batten Light

4 x Mounting Screws


4 x Rawl plugs/Expansion plugs

3 x Quick Fit Mounting Clips




1.)	Lens Cover
2.)	Waterproof Gasket
3.)	IP65 Termination In & Out
4.)	Quick Fit Mounting Clips
5.)	Mounting Screws
6.)	Expansion Plugs

This user manual, as well as the rating labels on the product, may show the following symbols. These symbols represent important information about the product or instructions on its use.

	This product is rated IP65, and suitable for exterior installations. The product must not be exposed to conditions beyond IP65 protection, this includes during cleaning e.g. water blasting, chem wash etc.
	Adjustable Colour Temperature.
 36W/48W/60W	Adjustable Power Output.
	
	Reference temperature of the ambient air when the product was tested to deliver the rated performance.
	Do not place the electrical item in the general waste (it should be taken to a local recycling centre).
	Conforms to safety and EMC standards.
	Indicates high voltage that could be dangerous to you and other persons operating this equipment. Read the message and follow the instructions carefully.
	Risk of personal injury, loss of life or damage to the lighting fixture in the event of non-observance of the instructions in this manual.


Specifications

Power Input	220-240V~ AC 50/60 Hz
Power Output	Adjustable 36W/48W/60W
Lumens	100 Lumens per Watt
Colour Temperature	Adjustable 3000 / 4000 / 5000K
Light Source	Integrated LEDs (not replaceable)
Dimmable	Non-Dimmable
CRI	80+
Ingress Protection	IP65
Beam Angle	120°
Material	Polycarbonate
Use	Indoor or Outdoor
Operating Position	Rigid Horizontal or Vertical surface
Estimated Hours	50,000 Hours / L90
Ambient Temp	ta -20° to 25°
Complies with	AS/NZS 60598-2-1




Installation Procedure


1. Before installing, ensure power to the circuit is isolated for the duration of the installation and all packaging materials are fully removed.




2. Select the appropriate mounting position. Pull quick fit clips out and slide along to desired location. Secure the quick fit clips to surface with screws provided.




3. Open one of the two terminal boxes to connect wiring. To do this pull out the side clips. The Second Terminal box can be used to link/loop to another light.




4. Connect wiring to the Batten. Brown (Active) wire to the contact marked 'L', Blue (Neutral) wire to 'N' & green/yellow wire to Earth 'E'. Clip the lid closed once done.



5. Select the desired power/light output and colour temperature, located inside the terminal boxes.



6. Clip Batten into place. Energise the circuit at the mains then turn the individual switch 'ON'. Your Batten light should now operate.



Warnings

- Always read the instructions carefully before installation, failure to do this could result in damage to the product, property or harm to the installer.
- This product should be installed by a licensed electrician in accordance with the Australian / New Zealand Wiring Rules AS/NZS 3000.
- It is recommended that this product be used on a circuit board protected by an Earth Leakage Circuit Breaker or Safety Switch.
- GOOD PRACTICE DOES NOT RECOMMEND THE 24/7 USE OF PRODUCTS WITHOUT THE APPLICATION OF SUITABLE SWITCH CYCLE INTERVALS. RECOMMENDED OPERATING HOURS, PRODUCT DESIGN EXPECTATIONS PROVIDE FOR A CONTINUAL DAILY USAGE OF 6 HOURS FOR RESIDENTIAL
- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or similar qualified person.
- Always use on rigid flat & level horizontal or vertical surfaces.
- Allow suitable ventilation around the light fitting and do not cover with any material.
- Do not immerse any part of the light fitting in water or any other liquids.
- Keep away from any flammable surface or materials.
- Always check for damage or worn parts before use.
- If damage is found cease use immediately and consult a professional electrician.
- Do NOT attempt to modify this fitting in any way.
- Do not stare directly into the lights. Prolonged exposure to bright lights could harm your eyes.
- Always use on rigid flat & level horizontal or vertical surfaces.
- This device should not be used by persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge unless they have been given supervision or instruction concerning use of this appliance in a safe way and understand the hazards involved.
- Do not stare directly into the lights, prolonged exposure to bright lights could harm your eyes
- This device should not be used by persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge unless they have been given supervision or instruction concerning use of this appliance in a safe way and understand the hazards involved.
- Store in a secure place, out of the reach of children. This is not a toy.

Before you begin

- Ensure power to the circuit is isolated for the duration of the installation.
- This product must be installed by a licensed electrician in accordance with the Australian / New Zealand Wiring Rules AS/NZS3000.
- When selecting a mounting location, choose an area where you can firmly attach to a solid support structure i.e. timber noggs, concrete wall. We do not recommend installing into areas without a solid structure.
- Check your mounting location carefully for concealed cables or pipes before beginning. You must be careful not to drill into or pierce a cable or pipe inside the wall structure.
- Always ensure the supporting surface will safely support the combined weight of the attached equipment and all attached hardware and components.
- Always double check your measurements and work before proceeding.
- Use a spirit level.
- Check you have the right tools and safety equipment to complete the installation.

Disposal

When this fixture is no longer used or required it should be disposed of with household waste. We recommend completing this in the most environmentally friendly way. Please recycle where facilities exist in your local area. Check with your council authority for recycling advice.

Recycling of packaging materials reduces the need for landfill. Please recycle packaging where possible. Check with your local council authority for recycling advice.

Cleaning, Maintenance & Storage

ALL PRODUCTS MUST BE THOROUGHLY CLEANED ON A REGULAR BASIS AT INTERVALS THAT ARE REFLECTIVE OF THE INSTALLATION ENVIRONMENT, ENSURING THE OPTICAL PERFORMANCE, TOGETHER WITH THE ELECTRICAL, MECHANICAL AND STRUCTURAL INTEGRITY AS DESIGNED, IS MAINTAINED THROUGHOUT THE SERVICE LIFE OF THE PRODUCT

Products installed in corrosive or salt laden environments require special consideration and extensive ongoing maintenance. A cleaning program should be adopted that maintains the design integrity of the product

Before cleaning ensure power to the circuit is isolated.

Clean regularly with a dry cloth.

Do not use solvents, abrasive cleaning materials or solutions.

Do Not submerge in liquid.

Store in a clean, dry location – out of reach of children.

Check regularly for damage, if found cease use immediately and contact a licensed electrician..

Proof of Purchase

Please retain your purchase receipt for all warranty claims

Warranty

Your product is warranted against faults and manufacture defects when used as per instruction for a period of three years.

We undertake to replace this product at no charge if found to be defective due to a manufacturing fault during the warranty period. This warranty excludes damage caused by misuse, neglect, shipping accident, incorrect installation, or work carried out by anyone other than a qualified electrical service technician. It also excludes liability for discolouration of paint or plastic, or any user serviceable parts. It does not confer any rights other than those expressly set out above and does not cover any claims for consequential loss or damage.

If your product fails to operate satisfactorily, please return it to the retailer from whom it was purchased to obtain a repair or replacement product. You will need to produce satisfactory evidence of date of purchase. If the product is to be replaced (cannot be repaired) then that replacement will be of the same or similar product or accessory excluding packaging, instruction card etc.

In New Zealand product is covered by the Consumers Guarantee Act (1993). In accordance with the act consumers are advised that: The manufacturer does not undertake that repair facilities and parts are necessarily available for this product.

In Australia, our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

Proof of Purchase

Please retain your purchase receipt for all warranty claims

Documents

ANY PRINTED DOCUMENTS WILL ONLY BE CORRECT AT THE TIME THEY ARE PRINTED
ALL DOCUMENTS ARE AVAILABLE VIA THE WEB AND WILL BE MAINTAINED TO ENSURE THEY ARE CURRENT.
Documents are ALSO AVAILABLE by using the [QR code](#) located on;

- Packaging
- Product

CDB  GROUP

New Zealand
PO Box 100-707
N.S.M.C
Auckland

Phone +64 (0)9 917 4000
Phone 0800 232 633
info@cdb.co.nz

Australia
PO Box 574
South Morang
Victoria, 3752

Phone +61 (0)3 9336 4423
Phone 1300 465 324
info@cdbgoldair.com.au