

AMBIUS

Mini Downlights



Ambius Mini Downlight Range with one driver running up to 6 downlights is a very cost-effective way to install multiple light fittings.

Range Includes:



Fixed - AMDLFIX



Eyeball - AMDLTLT



Eyelid - AMDLEYE



IP65 - AMDLIP



Cabinet - Recessed or Surface Mounted - AMDLCAB

Each downlight comes with 20cm cable & plug.

For convenience 4-piece kits with Mini Downlights, leads and drivers are also available on some models. Two additional Mini Downlights can be added to these kits.

The 36W driver (AMDLDR6) comes with easy, quick termination terminal block and a 6-plug adapter for connection to Mini Downlights.



5-meter extension cables (AMDLCAB5) are available which can be joined together (up to 20M) if required.



LIGHT SPECIFICATIONS

Wattage	3W Integrated LEDs
Colour Temp	3,000K
CRI	90+
Lifespan	L80 B10 59,000 hours
Material	Aluminium
Power Input	12V 270mA, 3W
Warranty	5 Years



3000K

Model No	Pronto Code	Lumens	UGR	IP Rating	Cut Out	Diameter	Height
AMDLCAB	Q5071220	200-250	22-23	IP44	28mm Recess Mount	40mm	26mm
AMDLCAB4PK	Q5071230	200-250	22-23	IP44	28mm Recess Mount	40mm	26mm
AMDLFIX	Q5071240	200-250	20	IP44	32mm	40mm	35mm
AMDLFIX4PK	Q5071250	200-250	20	IP44	32mm	40mm	35mm
AMDLIP	Q5071270	200-250	22-23	IP65	28mm	36mm	44mm
AMDLIP4PK	Q5071280	200-250	22-23	IP65	28mm	36mm	44mm
AMDLEYE	Q5071260	100-150	22-23	IP65	28mm	36mm	36mm
AMDLTLT	Q5071290	200-250	20	IP44	36mm	45mm	39mm

CABLE AND DRIVER SPECIFICATIONS

Model	Pronto Code	Description	IP Rating	Power
AMDLCAB5	Q5071310	5M EXTENSION CABLE	IP20	300V, 0.75m ²
AMDLDR6	Q5071320	DRIVER	IP20	Input : 90-265V 50/60Hz 0.35A, Output: DC12V Max 3A

Note: Each driver is equipped with 6 ports, and the maximum current of each port shall not exceed 2A.

